

Turf Fertilizer 14-0-24



with MUtech™ slow-release nitrogen

FEATURES & USE TIPS:

- Contains 65% MUtech slow release nitrogen
- Provides 2% iron and 5% manganese
- For use on greens and shortcut fairways
- SGN 125

PRODUCT SPECIFICATIONS:

N - (14%):	6.27% Urea Nitrogen 3.18% Water Insoluble Nitrogen 4.55% Other Water Soluble Nitrogen* <small>*4.55% slowly available nitrogen from methylene ureas</small>
K - as K₂O - (24%):	Potassium Sulfate
S - (8.16%):	Combined Sulfur
Fe - (2.00%):	Iron
Mn - (5.00%):	Manganese

Following is a specimen label that may at some point be revised or otherwise become out of date. It is intended as a guide in providing general information regarding the use of this product. Always read and follow the label on the product container.

PRODUCT CODE:

AGC14W5

Date: 042310
Supersedes: 020403
Label: G9

PRODUCT CHARACTERISTICS:

Product Type:

Fertilizer

Nitrogen Type:

MUtech™

Particle Size:

SGN: 125

Net Weight:

50 lbs.

Coverage:

12,500 sq. ft.
@ Medium Rate

Andersons Golf Products and Tee Time are registered trademarks of The Andersons, Inc.; MUtech is a trademark of The Andersons, Inc.

To order, contact your local Andersons Golf Products distributor.

For more information, contact Andersons at our website: www.andersonsgolfproducts.com or call 1-800-225-2639.

PRODUCT SHEET



Turf Fertilizer

14-0-24

with **MUtech™** slow-release nitrogen

- Contains iron and manganese
- SGN 125 for use on greens and short cut fairways

Guaranteed Analysis

Total Nitrogen (N)	14.00%
6.27% Urea Nitrogen	
3.18% Water Insoluble Nitrogen	
4.55% Other Water Soluble Nitrogen*	
Soluble Potash (K ₂ O)	24.00%
Sulfur (S)	8.16%
8.16% Combined Sulfur (S)	
Iron (Fe)	2.00%
Manganese (Mn)	5.00%
0.72% Water Soluble Manganese (Mn)	

Plant nutrients derived from urea, potassium sulfate, methylene ureas, manganese oxide and ferric oxide.

*4.55% slowly available nitrogen from methylene ureas

F292

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.regulatory-info-ap.com>.

DIRECTIONS FOR USE

Apply only as directed. Apply during the growing season.

Application Rates:

LOW:	2.0 lbs./1,000 sq. ft.
MEDIUM:	4.0 lbs./1,000 sq. ft.

FLORIDA APPLICATIONS: We recommend that you follow the Florida Green Industries BMP's at http://www.flaes.org/pdf/BMP_Book_final.pdf

FLORIDA APPLICATIONS: We recommend that you follow the Florida Golf Course BMP's at <http://www.flaes.org/pdf/gfbmp07.pdf>

For all applications:

- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to avoid particle pick-up.

Cool Season Grasses:

- Apply at the MEDIUM RATE.
- Apply at the LOW RATE when temperatures exceed 85°F.

Warm Season Grasses:

- Apply at the MEDIUM RATE every 4-6 weeks during the period of active growth.

Note: This product contains the micronutrient iron for extra greening and to help prevent iron deficiency. Iron may stain concrete and other surfaces. Misapplied product to these surfaces should be removed promptly by sweeping or blowing. **DO NOT WASH OFF WITH WATER.**

Recent research has shown that well-maintained turf is an effective environmental buffer that prevents pollutants from entering our natural water bodies. To help protect these natural resources, avoid applying product to sidewalks, driveways, roadways, and other impervious surfaces. Sweep any misplaced granules back onto the area you are treating immediately after application, since storm drains often empty directly to nearby waterways.

STORAGE AND USE

Store in a clean, dry place. Reseal opened bag by folding top down and securing. Use only in clean, dry spreaders. Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS. Use contrary to label directions is not permitted.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE JURISDICTION TO STATE JURISDICTION.

Product of U.S.A.

Manufactured by:
The Andersons Lawn Fertilizer Division, Inc.
P.O. Box 119
Maumee, OH 43537
www.andersonsgolfproducts.com

Andersons Golf Products and Tee Time are registered trademarks of The Andersons, Inc.; MUtech is a trademark of The Andersons, Inc.

Tee Time®

Suggested Spreader Settings


These suggested spreader settings are not intended to replace calibration. Please calibrate your spreader prior to applying product.

50 lbs. feeds 25,000 sq. ft. (0.57 acre) with 0.48 lbs. K₂O/1,000 sq. ft. at the LOW RATE
50 lbs. feeds 12,500 sq. ft. (0.29 acre) with 0.96 lbs. K₂O/1,000 sq. ft. at the MEDIUM RATE

SPREADER	GROUND SPEED	WIDTH OF COVERAGE	SPREADER SETTINGS	
			LOW RATE 2.0 lbs/1,000 sq. ft.	MEDIUM RATE 4.0 lbs/1,000 sq. ft.
Andersons AccuPro 2000, SR-2000 (cone 5)	3 mph	12 feet	1 1/4	J 1/2
Andersons SS-2 Drop	3 mph	overlap wheels	4 1/2	6
Scotts R-8, R-8A (cone 5)	3 mph	12 feet	H	I 1/2
Lesco 020093	3 mph	10 feet	C 1/2	E 1/2
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern III-B	4.5 mph	34 feet	3 3/4	5 1/4
Vicon (03 Series)	4.5 mph	28 feet	18	31

SGN 125

Net Wt. 50 Lbs. (22.68 kg)



0 31865 30895 6

AGC14W5

G9* (AGCBLKPMGRNB)